





SYNTHETIC ROOFING UNDERLAYMENT



Pro-Master Roof Shield UDL™ - Synthetic Roofing Underlayment

- UV Stabilized Synthetic Material Rated for One Year Exposure.
- Lightweight: 28 lbs. for 10 Sq. Roll.
- Printed with Nail Pattern and Alignment Guides.
- Anti-Slip Coated for Safety.
- 52" Width Makes Installation Quicker.
- Resists Mold.
- Stronger & Lighter than Organic Underlayment.
- 25 Year Limited Warranty.
- May be Used with: Asphalt Shingles, Wood Shakes, Non-Structural Metal Roofing, and Synthetic & Quarry Slate.
- Florida Building Code Approved for Use in HVHZ (High Velocity Hurricane Zone) as per TAS 104.

Woven Black Polypropylene with Polymer				
Roll Size	Size	Pallet Size	Code	Price
10 Square Roll	52" x 231'	49 Rolls	PMUDL10	



Pro-Master Roof Shield UDL PLUS™ - Synthetic Roofing Underlayment

- UV Stabilized Synthetic Material Rated for One Year Exposure.
- Lightweight: 30.3 lbs. for 10 Sq. Roll.
- Printed with Nail Pattern and Alignment Guides.
- Traction Twist Fiber™ for Safety - 30% Better Traction.
- 52" Width Makes Installation Quicker.
- Resists Mold.
- Stronger & Lighter than Organic Underlayment.
- 25 Year Limited Warranty.
- May be Used with: Asphalt Shingles, Wood Shakes, Tile Roofing, Non-Structural Metal Roofing, and Synthetic & Quarry Slate.
- Florida Building Code Approved for Use in HVHZ (High Velocity Hurricane Zone) as per TAS 104.

Woven Black Polypropylene with Polymer				
Roll Size	Size	Pallet Size	Code	Price
10 Square Roll	52" x 231'	36 Rolls	PMUDL10P	

SYNTHETIC ROOFING UNDERLAYMENT